

Web TCT Shell User Guide

Version 1.0, for Tizen 2.3.1

Copyright © 2015 Intel Corporation and Samsung Electronics Co., Ltd. All rights reserved. No portions of this document may be reproduced without the written permission of Intel Corporation.

Intel is a trademark of Intel Corporation in the U.S. and/or other countries.

Linux is a registered trademark of Linus Torvalds.

Tizen® is a registered trademark of The Linux Foundation.

ARM is a registered trademark of ARM Holdings Plc.

*Other names and brands may be claimed as the property of others.

Any software source code reprinted in this document is furnished under a software license and may only be used or copied in accordance with the terms of that license.

Contents

1	Introduction.....	3
2	Overview.....	3
3	Terminology.....	3
4	Prerequisites.....	4
5	Installing Web TCT Shell.....	4
6	Web TCT Shell Options.....	4
6.1	Mandatory Options	4
6.2	Optional Options.....	5
7	Typical Usage	6
7.1	Generating a Test Plan	6
7.2	Running Test	6
8	View Report	7

1 Introduction

This document provides comprehensive information about Web TCT Shell, including the following: Overview, Installation Instructions, Command Option Descriptions, and Typical Usage etc.

2 Overview

Web TCT Shell is a lightweight console tool and serves as a major component of the Tizen Compliance Tests (TCT) tool set. By providing an alternative way to execute the TCT tools with Testkit-lite, Web TCT Shell allows users to:

- Run test packages
- Run test plans
- Generate test reports
- Rerun failed tests
- Show test resources, such as plans, test results, and connected devices

3 Terminology

Test Package: .zip file that contains test cases.

Test Plan: .xml file that contains a series of test suites.

Test Report: .html file readable for users in the test result package.

Test Result: .xml file that contains the result information of a test execution.

4 Prerequisites

Make sure these items are in place before starting:

- One of these Linux distribution versions is installed:
 - Ubuntu 12.04 (32-bits)
 - Ubuntu 12.04 (64-bits)
 - Ubuntu 12.10 (32-bits)
 - Ubuntu 12.10 (64-bits)
 - Windows 7 (32-bits)
 - Windows 7 (64-bits)
- Web TCT Shell depends on Python and python-support (0.90.0 or later) is installed.
- Tizen capable devices with the latest the Tizen implementation (for example, M0 and Lunchbox) are available.
- The sdb software is correctly installed.
- There is a USB connection between the host and the target device.
- Enable “USB debugging” option in settings on target device
- Ensure the “unzip” command-line tool installed on target device.

5 Installing Web TCT Shell

Make sure the installation environment is ready before starting.

For detailed instructions, refer to chapter 4, "Installing Web TCT" in the *Web_TCT_2.3.1_User_Guide*.

6 Web TCT Shell Options

6.1 Mandatory Options

Mandatory options	
Option	Description
<code>--testplan/-p</code>	Specify testplan.xml as the test plan.
<code>--test/-t</code>	Specify testing suites. If more than one suite is provided, list them all and separate them with whitespace.
<code>--rerun-fail</code>	Rerun all failed test cases, according to the specified XML.

6.2 Optional Options

Optional options	
Option	Description
<code>--output=<i>resultfile</i></code>	Specify the output file for the resulting XML output. If more than one test xml file is provided, results will be merged into this output file.
<code>--version</code>	Show version information.
<code>--skip-iu</code>	Do not install and uninstall suite packages during a test. Install and uninstall them manually.
<code>--all-suites</code>	Show all available test-suites in the local repository. Its location is defined in the configuration file named CONFIG, and its path is: <code>/opt/tct/tizen_web_2.3.1/shell/CONFIG</code> .
<code>--deviceid</code>	Set sdb device serial information.
<code>--plan-list</code>	List all existing plans in the plan folder. The plan folder is defined in the configuration file named CONFIG, and its path is: <code>/opt/tct/tizen_web_2.3.1/shell/CONFIG</code> .
<code>--result-list</code>	List all history results in the result folder. The result folder is defined in the configuration file named CONFIG, and its path is: <code>/opt/tct/tizen_web_2.3.1/shell/ CONFIG</code> .
<code>--device-list</code>	List all connected devices.
<code>--all</code>	All test cases will be executed.
<code>--manual</code>	Only manual test cases will be executed.
<code>--id</code>	Specify the ID of a test case to run.
<code>-h, --help</code>	Show this help message and exit.

7 Typical Usage

7.1 Generating a Test Plan

Test plans	
Suites to include	Command
Include all suites in the local repository	<code>\$ tct-plan-generator -o <somewhere>/testplan.xml</code>
Include all suites in the special repository	<code>\$ tct-plan-generator -o <somewhere>/testplan.xml -r <somewhere>/repository_folder</code>
Include the suites in the special repository where the name matches a specific regular expression	<code>\$ tct-plan-generator -o <somewhere>/testplan.xml -r <somewhere>/repository_folder --match '<regex>'</code>
Include the suites in the special repository where the name matches a specific regular expression, and exclude any file where the name matches another regular expression	<code>\$ tct-plan-generator -o <somewhere>/testplan.xml -r <somewhere>/repository_folder --match '<regex>' --unmatch '<unmatch_regex>'</code> For example, to exclude the Testkit-stub package: <code>\$ tct-plan-generator -o <somewhere>/testplan.xml -r <somewhere>/repository_folder --match '*.rpm' --unmatch 'stub'</code>

7.2 Running Test

Running tests	
Function	Command
Show the help information	<code>\$ tct-shell --help</code>
Show the plan list	<code>\$ tct-shell --plan-list</code> Test plans are placed in the '/opt/tct/tizen_web_2.3.1/shell/plan' folder, by default. Edit the '/opt/tct/tizen_web_2.3.1/shell/CONFIG' file to change it, if necessary: <code>TCT_PLAN_FOLDER = <path-to-plans></code>
Show the package list	<code>\$ tct-shell --all-suites</code> The default package repository is in the /opt/tct/tizen_web_2.3.1/packages folder. Edit '/opt/tct/tizen_web_2.3.1/shell/CONFIG' file to change it, if necessary: <code>TEST_SUITE_DIR = <path-to-suites></code>

Running tests	
Function	Command
Show the test result list	<pre>\$ tct-shell --result-list</pre> Each test result is generated as a separate folder in the /opt/tct/tizen_web_2.3.1/shell/result folder.
Show the device list:	<pre>\$ tct-shell --device-list</pre>
Run a test plan	<pre>\$ tct-shell --testplan '<somewhere>/testplan.xml'</pre>
Run some test packages	<pre>\$ tct-shell --test 'package1 package2 ... packageN'</pre>
Run a test case by its ID:	<pre>\$ tct-shell --test 'package' --id <case-id></pre>
Rerun all failed test cases	<pre>\$ tct-shell --rerun-fail '<somewhere>/test-result.xml'</pre>
Install and uninstall suite packages manually	Do not install and uninstall suite packages during a test (they need to be installed and uninstalled manually): <pre>\$ tct-shell --testplan '<somewhere>/testplan.xml' --skip- iu</pre>
Run a test package on a specific device:	<pre>\$ tct-shell --testplan '<somewhere>/testplan.xml' -- deviceid<device-id></pre>
Run all test cases, including automatic and manual cases	<pre>\$ tct-shell --testplan '<somewhere>/testplan.xml' --all</pre>
Run manual test cases	<pre>\$ tct-shell --testplan '<somewhere>/testplan.xml' -- manual</pre>
Specify the output file for test results	<pre>\$ tct-shell --testplan '<somewhere>/testplan.xml' -o <somewhere>/test-result.xml</pre>

8 View Report

Test result is placed in /opt/tct/tizen_web_2.3.1/shell/result, in a new folder, with the test date-time string as the name. To view the result, navigate to the test result folder and open the summary.xml file with the web browser. This is a sample file:

TCT Report

Test Summary		Device Information	
Test Plan Name	Full_test	Host Device	Linux-3.5.0-17-generic-i686-with-Ubuntu-12.10-quantal
Build ID	Tizen_Ref Device-PQ_20131022.1656	Manufacturer	samsung
Test Total	994	Device Model	RD-PQ
Test Passed	981	Device ID	4d700de66263000
Test Failed	1	Screen Size	58mm x 103mm
Test Blocked	12	Resolution	720 x 1280
Test Not Executed	0		
Time	2013-10-25_10_18_31 ~ 2013-10-25_10_24_02		

Device Capability**Test Summary by Suite**

Suite	Total	Passed	Failed	Blocked	Not Executed	Ratio
tct-2dtransforms-css3-tests	34	34	0	0	0	100.00%
tct-appcontrol-tizen-tests	5	5	0	0	0	100.00%

Click on the suite name in the Test Summary by Suite table to see details.

This is an example of the test suite's details:

Suite Test Results

[Show all](#)
[Show only failed](#)
[Show only blocked](#)
[Show only not executed](#)
[Summary](#)

Test Suite: tct-capability-tests (All)

Case_ID	Purpose	Result	Stdout
Test Set: capability			
caps_accelerometer	Check if accelerometer is supported on the device	FAIL	[Message]###Test Start###Capability Test: caps_accelerometer###Test End#####Error2 Start###assert_true: accelerometer capability is mismatched expected true got false(stack: assert@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:2022 assert_true@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:615 check_capability@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/support/caps.js:329 file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_accelerometer.html:49 step@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:1121 test@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:414 global code@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_accelerometer.html:50)###Error2 End###
caps_barometer	Check if barometer is supported on the device	PASS	[Message]
caps_bluetooth	Check if bluetooth is supported on the device	FAIL	[Message]###Test Start###Capability Test: caps_bluetooth###Test End#####Error2 Start###assert_true: bluetooth capability is mismatched expected true got false(stack: assert@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:2022 assert_true@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:615 check_capability@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/support/caps.js:329 file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_bluetooth.html:52 step@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:1121 test@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:414 global code@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_bluetooth.html:53)###Error2 End###

Click on the corresponding link, at the top of the page, to filter the failed, blocked, or not executed test cases.

This is an example of the filtered information:

Suite Test Results

[Show all](#)
[Show only failed](#)
[Show only blocked](#)
[Show only not executed](#)
[Summary](#)

Test Suite: tct-capability-tests (Failed only)

Case_ID	Purpose	Result	Stdout
Test Set: capability			
caps_accelerometer	Check if accelerometer is supported on the device	FAIL	[Message]###Test Start###Capability Test: caps_accelerometer###Test End#####Error2 Start###assert_true: accelerometer capability is mismatched expected true got false(stack: assert@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:2022 assert_true@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:615 check_capability@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/support/caps.js:329 file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_accelerometer.html:49 step@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:1121 test@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:414 global code@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_accelerometer.html:50)###Error2 End###
caps_bluetooth	Check if bluetooth is supported on the device	FAIL	[Message]###Test Start###Capability Test: caps_bluetooth###Test End#####Error2 Start###assert_true: bluetooth capability is mismatched expected true got false(stack: assert@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:2022 assert_true@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:615 check_capability@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/support/caps.js:329 file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_bluetooth.html:52 step@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:1121 test@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/resources/testharness.js:414 global code@file:///opt/usr/apps/api0capab0/res/wgt/opt/tct-capability-tests/capability/caps_bluetooth.html:53)###Error2 End###